
SPECIFICATIONS

DIMENSION

Width	10 3/8 inches	(264 mm)
Depth	25 1/4 inches	(641 mm)
Height (without legs)	22 15/16 inches	(583 mm)

WEIGHT

Shipping	108 pounds	(49.0 kg)
Empty	89 pounds	(40.4 kg)
Operating	125 pounds	(55.4 kg)

Please refer to the Lancer web site (www.lancercorp.com) for information relating to Lancer Installation and Service Manuals, Instruction Sheets, Technical Bulletins, Service Bulletins, etc.

WATER REQUIREMENTS

CAUTION

IF WATER SOURCE EXCEEDS 60 PSIG (4.22 KG/CM²), A RECOMMENDED WATER REGULATOR ASSEMBLY (PN 18-0253) MUST BE USED TO LIMIT WATER PRESSURE TO 60 PSIG (4.22 KG/CM²). FAILURE TO USE REGULATOR WILL RESULT IN IMPROPER PERFORMANCE OF DISPENSER.

Minimum flowing pressure of 35 PSIG (2.46 kg/cm², 2.41 BAR)

Maximum static pressure of 60 PSIG (4.22 kg/cm², 4.14 BAR)

CARBON DIOXIDE (CO₂) REQUIREMENTS

Minimum pressure of 70 PSIG (4.92 kg/cm², 4.83 BAR)

Maximum pressure of 80 PSIG (5.62 kg/cm², 5.52 BAR)

ICE BANK WEIGHT	16 pounds	(17.26 kg)
WATER BATH CAPACITY	5.1 gallons	(19.3 liters)
COMPRESSOR	¼ HP Tecumseh, 115V/60Hz	
AGITATOR MOTOR	15W, 115V	
CONDENSER FAN MOTOR	9W, 115V	
ICE BANK CONTROL	Lancer Electronic Ice Bank Control	
TRANSFORMER	Basler, 115V (Primary)/24V (Secondary)	

Optional 230V/50Hz and 240V/60Hz systems available.

DRINK CAPACITY

57 – 12 ounce drinks under 40°F (4.4°C) at four (4) drinks per minute with 75°F (23.9°C) ambient, inlet water, and inlet syrup.

